

A141MCA2

More Confidential

$\sqrt{Ra6.3}$ ($\sqrt{Ra0.4}$)

$\Delta 700$

$\Delta 28$

7.5

2

D

D

M15X1P

MD15 $_{-0.026}^{-0.206}$

PD14.35 $_{-0.144}^{-0.026}$


$\phi 13$

$\phi 17_{-0.1}^0$

WIPER THIS END

(單邊附刮刷器)

($\phi 10$)



D-D VIEW

PRELOAD(kgf)	~
R.D.	8.348
S.F. (kgf)	~
DRAG TORQUE(kgf-cm)	~
DIRECTION OF TURN	R
P.C. DIA.	9.91
BALL DIA.	1.5
BACKLASH	0.01MAX
CIRCUIT	2.6*1
LEAD ANGLE	3.68
DYNAMIC (kgf)	250
STATIC (kgf)	500
LEAD	2

SPEC: R10-2B1-RSZ-700-700-0.05

MAX. AXIAL LOAD (kgf)		LUBRICATION		BALL DIA.	1.5
MAX. ROTATIONAL SPEED (rpm)		SPACE BALL		BACKLASH	0.01MAX
DN VALUE		E1 TYPE ASSEMBLY METHOD		CIRCUIT	2.6*1
MAX. FEED RATE (m/min)		CUSTOMER DRAWING NO.		LEAD ANGLE	3.68
ACCELERATION (m/sec ²)		CUSTOMER MC TYPE		DYNAMIC (kgf)	250
SUPPORT METHOD		CUSTOMER AXIAL TYPE		STATIC (kgf)	500
				LEAD	2

	UNCHAMFERED USE <input checked="" type="checkbox"/> C0.5 <input type="checkbox"/> C1 <input type="checkbox"/> C	SCALE	MAT.	SH:CF53/Equivalent	DATE	2021.05.03
	ROUGH M/C/FIN M/C/GRD	$\sqrt{Ra25}$ $\sqrt{Ra6.3}$ $\sqrt{Ra0.4}$	1: X	INT:SNM220/Equivalent	DWG	Melanie
	NORMAL TOLERANCE mm		THREAD BALL TRACK	CHK	Shower	
	UP TO	6 30 120 300 600 1200 2400	HRC 56 ~ 62	APPD	Sting	
	$\epsilon/300p$:	0.05	CUSTR		H-CHICAGO	
	ϵp :	$\Delta 0.117$	DWG.NO.		A141MCA2	

*BREAK SHARP EDGE UNLESS OTHER SPECIFIED.
*未量倒角者去毛邊 (CO.2MAX)
THREAD END ALLOWS ABOVE LENGTH OUT OF HARDNESS TOLERANCE

2021.05.03	MOD.	Δ \sim Δ	Sting
DATE	MODIFICATION	APPROVED	

* PLEASE IGNORE CHINESE CHARACTERS WHICH ARE FOR OUR REFERENCE ONLY.

HIWIN BALLSCREWS