



SPEC:R16-5.08T3-FS1

MAX. AXIAL LOAD (kgf)	LUBRICATION	PRELOAD (kgf)	~
MAX. ROTATIONAL SPEED (rpm)	SPACE BALL	R.D	~
DN VALUE	E1 TYPE ASSEMBLY METHOD	S.F (kgf)	~
MAX. FEED RATE (m/min)	CUSTOMER DRAWING NO.	DRAG TORQUE (kgf-cm)	~
ACCELERATION (m/sec <sup>2</sup> )	CUSTOMER MC TYPE	DIRECTION OF TURN	R
SUPP-RT METHOD	CUSTOMER AXIAL TYPE	PC DIA.	16.2
		BALL DIA.	3.175
		BACKLASH	△ 0.03MAX
		CIRCUIT	3
		LEAD ANGLE	5.7
		DYNAMIC (kgf)	664
		STATIC (kgf)	1196
		LEAD	5.08

<input type="checkbox"/> UNCHAMFERED USE <input type="checkbox"/> R0.5 <input checked="" type="checkbox"/> R1 <input type="checkbox"/> R	<input type="checkbox"/> GRD <input type="checkbox"/> 0.4g <input type="checkbox"/> 0.2g	<input type="checkbox"/> SH: ROLLED <input checked="" type="checkbox"/> NT: SNCV220/SCM415	DATE	2007.07.16
THREAD LENGTH E300: ~	UNTOOL DIMM mm TOP: 16 30 120 300 600 1200 OVER 19 4 30 20 300 600 1200 2400 ±1 ±0.2 ±1.3 ±0.4 ±0.5 ±0.8 ±1.1 ±1.5	MA T THREAD BALL TRACK HRC 56 ~ 62	DWG	JANET
CUSTR H-CHICAGO		APPD MICHELLE PROCESS NO. G	DWG.NO. A1141JB2	

2007.07.16	MOD. △	MICHELLE
DATE	MODIFICATION	APPROVED

\* PLEASE IGNORE CHINESE CHARACTERS WHICH ARE FOR OUR REFERENCE ONLY.

\* BREAK SHARP EDGE, UNLESS OTHER SPECIFIED  
 \* 未畫倒角者以R0.5MAX  
 ● THREAD END ALLOWS ABOVE LENGTH OUT OF HARDNESS TOLERANCE