



M34X1.5P
MD34- $\begin{smallmatrix} -0.032 \\ -0.268 \end{smallmatrix}$
PD33.026- $\begin{smallmatrix} -0.032 \\ -0.182 \end{smallmatrix}$

C0.2

φ31.5

φ36- $\begin{smallmatrix} -0.1 \\ -0.3 \end{smallmatrix}$

WIPER BOTH ENDS

PRELOAD(kgf)	~
R.D	~
S.F (kgf)	~
DRAG TORQUE(kgf-cm)	~
DIRECTION OF TURN	R
PC DIA.	20.2
BALL DIA.	3.175
BACKLASH	△ 0.03MAX
CIRCUIT	4
LEAD ANGLE	4.58
DYNAMIC (kgf)	938
STATIC (kgf)	1993
LEAD	5.08

SPEC:R20-5.08T4-RS1

MAX. AXIAL LOAD(kgf)	LUBRICATION	
MAX. ROTATIONAL SPEED (rpm)	SPACE BALL	
DIN VALUE	E1 TYPE ASSEMBLY METHOD	
MAX. FEED RATE(m/min)	CUSTOMER DRAWING NO.	
ACCELERATION(m/sec ²)	CUSTOMER MC TYPE	
SUPPORT METHOD	CUSTOMER AXIAL TYPE	
		STATIC (kgf) 1993
		LEAD 5.08

<p>E300: ~</p>	<input type="checkbox"/> R0.5 <input checked="" type="checkbox"/> R1 <input type="checkbox"/> R UNCHAMFERED USE	<input type="checkbox"/> GRD <input type="checkbox"/> 1: X SCALE	SH: ROLLED DATE 2007.07.16 INT: SNCM220/SCM415 DWG .ANET
	MA AL THREAD B.A.L TRACK HRC 56 ~ 62 APPD MICHELLE PROCESS NO. G	CUSTR H-CHICAGO DWG.NO. A114IUB5	

*BREAK SHARP EDGE UNLESS OTHER SPECIFIED
*未書利角者以R0.5MAX
● THREAD END ALLOWS ABOVE LENGTH OUT OF HARDNESS TOLERANCE

2007.07.16	MOD. △	MICHELLE
DATE	MODIFICATION	APPROVED

* PLEASE IGNORE CHINESE CHARACTERS WHICH ARE FOR OUR REFERENCE ONLY.

HIWIN BALLSCREWS